



US009192060B2

(12) **United States Patent**
Kawasaki

(10) **Patent No.:** **US 9,192,060 B2**
(45) **Date of Patent:** **Nov. 17, 2015**

(54) **ELECTRONIC DEVICE**

USPC 455/575.3
See application file for complete search history.

(75) Inventor: **Yasuhiko Kawasaki**, Kanagawa (JP)

(73) Assignee: **NEC CORPORATION**, Tokyo (JP)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(56) **References Cited**

U.S. PATENT DOCUMENTS

5,987,704 A * 11/1999 Tang 16/354
6,519,812 B2 * 2/2003 Ko et al. 16/354

(Continued)

FOREIGN PATENT DOCUMENTS

JP 2005-155750 6/2005
JP 2009-141750 6/2009

(Continued)

OTHER PUBLICATIONS

International Search Report corresponding to PCT/JP2012/004600, dated Aug. 14, 2012; 1 page.

Primary Examiner — Kwasi Karikari

(74) *Attorney, Agent, or Firm* — Wilmer Cutler Pickering Hale and Dorr LLP

(21) Appl. No.: **14/345,604**

(22) PCT Filed: **Jul. 19, 2012**

(86) PCT No.: **PCT/JP2012/004600**

§ 371 (c)(1),

(2), (4) Date: **Mar. 18, 2014**

(87) PCT Pub. No.: **WO2013/042296**

PCT Pub. Date: **Mar. 28, 2013**

(65) **Prior Publication Data**

US 2014/0355216 A1 Dec. 4, 2014

(30) **Foreign Application Priority Data**

Sep. 21, 2011 (JP) 2011-205787

Sep. 21, 2011 (JP) 2011-205788

(51) **Int. Cl.**

H04M 1/00 (2006.01)

H05K 5/00 (2006.01)

(52) **U.S. Cl.**

CPC **H05K 5/00** (2013.01)

(58) **Field of Classification Search**

CPC H04M 1/0214; H04M 1/0212; H04M 1/0227; H04M 1/0233; H04M 1/0247; H04M 2250/16; H04M 1/0216; H04M 1/0218; H04M 1/0225; H04M 1/0243; G06F 1/1616; G06F 1/1681; G06F 1/1622; G06F 1/1613

(57)

ABSTRACT

The electronic device includes a first casing, a second casing, and a connecting member engaging with the first casing to allow the first casing to turn about a first axis of rotation, and engaging with the second casing to allow the second casing to turn about a second axis of rotation. When a turning angle is 0 or 360 degrees, a distance between the first and second axes of rotation equals to the sum of a half of the sum of the thicknesses of the first and second casings and a clearance between the first and second casings, and the first axis of rotation is arranged at a position shifted from the center of the first casing in a reference direction to the second casing side, by a half of a value calculated by subtracting the thickness of the first casing from the thickness of a first casing-side connecting portion.

11 Claims, 35 Drawing Sheets

